

Certificate of Compliance



This is a certificate of compliance to certify that the bearer has successfully completed the requirements of the above scheme which include the testing of products, the initial assessment, and are subject to continuing annual assessments of their compliance and testing of samples of products taken from production (as applicable to the scheme) and has been registered within the scheme for the products detailed.

You have been awarded:

Intertek Warnock Hersey Mark for fire resistant doors and door sets

Standard(s): UL 10(b) (2008), UL 10(c) (2009), UL 10(b) (2009), CAN / ULC S104 (2010), NFPA 252 (2012), CAN / ULC S104 (2015), UL 10(c) (2016), NFPA 252 (2017)

Certificate number: WHI17 – 9354714

Organization:

Haseeb Rasoul FZC

P.O. Box 42327

Hamriyah Free Zone

Sharjah, United Arab Emirates

Product: Warm Springs - 20 Minute Solid Core Fire Door (SPEC ID 30396)

Maximum sizes 20 minutes

Single Swing: 4'0" wide x 9'0" high (1219mm wide x 2743mm high)

Standard Pairs: 8'0" wide x 9'0" high (2438mm wide x 2743mm high)

Standard Pairs (Single Leaf): 4'0" wide x 9'0" high (1219mm wide x 2743mm high)

Double Egress Pairs: Not Allowed

Door and Transom: Not Allowed

Dutch Door: Not Allowed

Minimum Thickness

All doors unless otherwise stated is 1-3/4" +/- 1/16"

Note: Pairs must have metal meeting edges.

Certification body: Intertek Testing Services NA, Inc.

Initial registration: August 01, 2017

Date of expiry: December 31, 2019


Issue status: 4

Charles Meyers
Certification Manager
Name


Signature

17 Mar 2019
Date

Certificate of Compliance



You have been awarded:

Intertek Warnock Hersey Mark for fire resistant doors and door sets

Standards: UBC 7-2 (1997), UBC 7-2 (1994), CAN / ULC S104 1980 (R1985), ASTM E2074 (2004), UL 10(b) (2008), NFPA 252 (2008), UL 10(c) (2001), UL 10(b) Revision 1 (2009), UL 10(c) (2009), CAN / ULC S104 (2010), NFPA 252 (2012)

Certificate number: WHI17 – 9354715

This is a certificate of compliance to certify that the bearer has successfully completed the requirements of the above scheme which include the testing of products, the initial assessment, and are subject to continuing annual assessments of their compliance and testing of samples of products taken from production (as applicable to the scheme) and has been registered within the scheme for the products detailed.

Organization:

Haseeb Rasoul FZC

P.O. Box 42327

Hamriyah Free Zone

Sharjah, United Arab Emirates

Product: Warm Springs 45-90 Minute Flush Doors

(SPEC ID 30393)

Composite Core Type, Swinging Flush Design Fire Door for installation in single swing or standard pairs 45 to 90 Minute locations

For details related to maximum dimensions and allowable configurations, see Appendix A (page 2 of 2 of this certificate)

Certification body: Intertek Testing Services NA, Inc.

Initial registration: August 01, 2017

Date of expiry: December 31, 2019

Issue status: 4

Charles Meyers
Certification Manager
Name

Signature

17 Mar 2019
Date

Certificate of Compliance WHI17 – 9354715

Appendix A

Maximum Sizes (by Core Type)

Thermal-Lite	Single	4'0" wide x 8'0" high
		3'0" wide x 8'0" high*
	Pairs	6'0" wide x 7'0" high**
		7'0" wide x 8'0" high***
MDS Mineral Core	Single	4'0" wide x 9'0" high
	Pairs	8'0" wide x 9'0" high****
AHI	Single	4'0" wide x 9'0" high
	Pairs	8'0" wide x 9'0" high****
G-P Gypsum	Single	4'0" wide x 8'0" high
	Pairs	8'0" wide x 8'0" high
WSCP-412	Single	4'0" wide x 8'0" high
	Pairs	8'0" wide x 8'0" high*

*Additional requirements as noted in manufacturing section

**3-point latching and 5" Tectonite meeting stile required

***4-point latching and 2" Tectonite stiles required

****4-point latching and 5" Tectonite stiles required for pairs over 8 ft. in height.

Certificate of Compliance



You have been awarded:

Intertek Warnock Hersey Mark for fire resistant doors and door sets

Standard(s): NFPA 252 (2008), UL 10(c) (2009), CAN / ULC S104 (2010), NFPA 252 (2012)

Certificate number: WHI17 – 9354716

This is a certificate of compliance to certify that the bearer has successfully completed the requirements of the above scheme which include the testing of products, the initial assessment, and are subject to continuing annual assessments of their compliance and testing of samples of products taken from production (as applicable to the scheme) and has been registered within the scheme for the products detailed.

Organization:

Haseeb Rasoul FZC

P.O. Box 42327

Hamriyah Free Zone

Sharjah, United Arab Emirates

Product: Warm Springs 60 and 90 Minute Profiled Core Fire Door (SPEC ID 30392)

Maximum sizes 60 minutes

Single Swing: 3'0" wide x 8'0" high

Standard Pairs: 6'0" wide x 7'0" high

Maximum sizes 90 minutes

Single Swing: 3'0" wide x 7'0" high

Pairs: Not allowed.

Minimum Thickness:

1-3/4 in.

Certification body: Intertek Testing Services NA, Inc.

Initial registration: August 01, 2017

Date of expiry: December 31, 2019

Issue status: 4

Charles Meyers
Certification Manager
Name


Signature

17 Mar 2019
Date

www.intertek.com

Registered address:
Intertek Testing Services NA, Inc. 545 E. Algonquin Rd. Arlington Heights, IL 60005 USA

The certificate and schedule are held in force by regular annual surveillance visits by Intertek Testing Services NA, Inc. and the reader or user should contact Intertek to validate its status. This certificate remains the property of Intertek Testing Services NA, Inc. and must be returned to them on demand. This Certificate is for the exclusive use of Intertek's Client and is provided pursuant to the Certification agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this certificate. Only the Client is authorized to permit copying or distribution of this certificate and then only in its entirety. Use of Intertek's Certification mark is restricted to the conditions laid out in the agreement. Any further use of the Intertek name for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. Initial Factory Assessments and Follow up Services are for the purpose of assuring appropriate usage of the Certification mark in accordance with the agreement, they are not for the purposes of production quality control and do not relieve the Client of their obligations in this respect.

Certificate of Compliance



You have been awarded:

Intertek Warnock Hersey Mark for fire resistant doors and door sets

Standard(s): ASTM E152-81a, UL 10(c) (1998), UBC 7-2 (1997), UBC 7-2 (1994), UL 10(b) (1997), ASTM E2074 (2000), NFPA 252 (2003), CAN / ULC S104 1980 (R1985), UL 10(b) Revision 1 (2009), UL 10(c) (2009), CAN / ULC S104 (2010), NFPA 252 (2012)

Certificate number: WHI17 – 9354717

This is a certificate of compliance to certify that the bearer has successfully completed the requirements of the above scheme which include the testing of products, the initial assessment, and are subject to continuing annual assessments of their compliance and testing of samples of products taken from production (as applicable to the scheme) and has been registered within the scheme for the products detailed.

Organization:

Haseeb Rasoul FZC

P.O. Box 42327

Hamriyah Free Zone

Sharjah, United Arab Emirates

Product: Warm Springs 60 Min Single-Swing MDF Door Frame (SPEC ID 30391)

Category C "Proprietary Frame" - Composite Door Frame for installation in 60 minute locations in steel/wood stud drywall or masonry openings. A Category B or Neutral Pressure fire rated wood/composite door may be used. Category G Edge Sealing System is not required. May be veneered or faced with HPL. Frame may also be used as a communicating frame.

Maximum sizes 60 minutes

Single Swing: 4'0" wide x 8'0" high

Throat Opening: 4-3/4 in.

Certification body: Intertek Testing Services NA, Inc.

Initial registration: August 01, 2017

Date of expiry: December 31, 2019

Issue status: 4

Charles Meyers
Certification Manager
Name


Signature


17 Mar 2019
Date

www.intertek.com

Registered address:
Intertek Testing Services NA, Inc. 545 E. Algonquin Rd. Arlington Heights, IL 60005 USA

The certificate and schedule are held in force by regular annual surveillance visits by Intertek Testing Services NA, Inc. and the reader or user should contact Intertek to validate its status. This certificate remains the property of Intertek Testing Services NA, Inc. and must be returned to them on demand. This Certificate is for the exclusive use of Intertek's Client and is provided pursuant to the Certification agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this certificate. Only the Client is authorized to permit copying or distribution of this certificate and then only in its entirety. Use of Intertek's Certification mark is restricted to the conditions laid out in the agreement. Any further use of the Intertek name for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. Initial Factory Assessments and Follow up Services are for the purpose of assuring appropriate usage of the Certification mark in accordance with the agreement, they are not for the purposes of production quality control and do not relieve the Client of their obligations in this respect.

Certificate of Compliance



You have been awarded:

Intertek Warnock Hersey Mark for fire resistant doors and door sets

Standard(s): ASTM E152-81a, UL 10(c) (1998), UBC 7-2 (1997), UBC 7-2 (1994), UL 10(b) (1997), ASTM E2074 (2000), NFPA 252 (2003), CAN / ULC S104 1980 (R1985), UL 10(b) Revision 1 (2009), UL 10(c) (2009), CAN / ULC S104 (2010), NFPA 252 (2012)

Certificate number: WHI17 – 9354718

This is a certificate of compliance to certify that the bearer has successfully completed the requirements of the above scheme which include the testing of products, the initial assessment, and are subject to continuing annual assessments of their compliance and testing of samples of products taken from production (as applicable to the scheme) and has been registered within the scheme for the products detailed.

Organization:

Haseeb Rasoul FZC
P.O. Box 42327
Hamriyah Free Zone
Sharjah, United Arab Emirates

Product: Warm Springs 20 Minute Fire Door Frame (with Concealed Closer) (SPEC ID 30394)

Category C "Proprietary Frame" - Composite Door Frame for installation in 20 minute locations in steel/wood stud drywall or masonry openings. A Category B or Neutral Pressure fire rated wood/composite door may be used. Category G Edge Sealing System is not required. May be veneered or faced with HPL. Frame may also be used as a communicating frame. Concealed closer allowed. (LCN 2030 Series)

Maximum sizes 20 minutes

Single Swing: 4'0" wide x 8'0" high
Standard Pairs: 7'0" wide x 8'0" high
Throat Opening: 4-3/4 in.

Certification body: Intertek Testing Services NA, Inc.

Initial registration: August 01, 2017

Date of expiry: December 31, 2019

Issue status: 4

Charles Meyers
Certification Manager
Name

Signature

17 Mar 2019
Date

Certificate of Compliance



This is a certificate of compliance to certify that the bearer has successfully completed the requirements of the above scheme which include the testing of products, the initial assessment, and are subject to continuing annual assessments of their compliance and testing of samples of products taken from production (as applicable to the scheme) and has been registered within the scheme for the products detailed.

You have been awarded:

Intertek Warnock Hersey Mark for fire resistant doors and door sets

Standard(s): UBC 7-2 (1994), ASTM E152-81AE02, NFPA 252 (2008), UL 10(b) Revision 1 (2009), CAN / ULC S104 (2010), NFPA 252 (2012)

Certificate number: WHI17 – 9354719

Organization:

Haseeb Rasoul FZC
P.O. Box 42327
Hamriyah Free Zone
Sharjah, United Arab Emirates

Product: Warm Springs Doors NP (SPEC ID 30369)

Mineral Core Type, Swinging Flush Design Fire Door for installation in single swing 90 Minute

Maximum Size of Openings: 4'0" wide x 8'0" high

Composite Core Type, Swinging Flush Design Fire Door for installation in single swing 90 Minute

Maximum Size of Openings: 4'0" wide x 8'0" high

Mineral Core Type, Swinging Flush Design Fire Door for installation in pairs in 60 Minute.

Maximum Size of Openings: 8'0" wide x 8'0" high

Vertical Rod Fire Exit Hardware and Metal Edges required.

Certification body: Intertek Testing Services NA, Inc.

Initial registration: August 01, 2017

Date of expiry: December 31, 2019

Issue status: 4

Charles Meyers
Certification Manager
Name


Signature

17 Mar 2019
Date

www.intertek.com

Registered address:
Intertek Testing Services NA, Inc. 545 E. Algonquin Rd. Arlington Heights, IL 60005 USA

Certificate of Compliance



You have been awarded:

Intertek Warnock Hersey Mark for fire resistant doors and door sets

Standard(s): ASTM E152-81a, UL 10(c) (1998), UBC 7-2 (1997), UBC 7-2 (1994), UL 10(b) (1997), ASTM E2074 (2000), NFPA 252 (2003), CAN / ULC S104 1980 (R1985), UL 10(b) Revision 1 (2009), UL 10(c) (2009), CAN / ULC S104 (2010), NFPA 252 (2012)

Certificate number: WHI17 – 9354720

This is a certificate of compliance to certify that the bearer has successfully completed the requirements of the above scheme which include the testing of products, the initial assessment, and are subject to continuing annual assessments of their compliance and testing of samples of products taken from production (as applicable to the scheme) and has been registered within the scheme for the products detailed.

Organization:

Haseeb Rasoul FZC

P.O. Box 42327

Hamriyah Free Zone

Sharjah, United Arab Emirates

Product: Warm Springs 20 Min Fire Door Frame

(SPEC ID 30395)

Category C "Proprietary Frame" - Composite Door Frame for installation in 20 minute locations in steel/wood stud drywall or masonry openings. A Category B or Neutral Pressure fire rated wood/composite door may be used. Category G Edge Sealing System is not required. May be veneered or faced with HPL. Frame may also be used as a communicating frame.

Maximum sizes 20 minutes

Single Swing: 4'0" wide x 8'0" high

Standard Pairs: 7'0" wide x 8'0" high

Throat Opening: 4-3/4 in.

Certification body: Intertek Testing Services NA, Inc.

Initial registration: August 01, 2017

Date of expiry: December 31, 2019

Issue status: 4

Charles Meyers
Certification Manager


Name

Signature

17 Mar 2019

Date

Certificate of Compliance



You have been awarded:

Intertek Warnock Hersey Mark for fire resistant doors and door sets

Standard(s): UL 10(c) (2009), UL 10(b) (2009), CAN / ULC S104 (2010), NFPA 252 (2012)

Certificate number: WHI17 – 9354721

This is a certificate of compliance to certify that the bearer has successfully completed the requirements of the above scheme which include the testing of products, the initial assessment, and are subject to continuing annual assessments of their compliance and testing of samples of products taken from production (as applicable to the scheme) and has been registered within the scheme for the products detailed.

Organization:

Haseeb Rasoul FZC

P.O. Box 42327

Hamriyah Free Zone

Sharjah, United Arab Emirates

Product: Warm Springs 60-90 minute Single Swing Sound Transmission Doorset (SPEC ID 35497)

Single-Swing Door maximum dimensions:

For 60 minutes: Maximum 48 in. wide by 96 in. high

For 90 minutes: Maximum 36 in. wide by 96 in. high

For 90 minutes: Maximum 42 in. wide by 84 in. high

All doors have a minimum thickness of 2-5/16 in. inclusive of the skins.

Notes:

- 1 - Pairs are not allowed
- 2 - These doors are eligible for use in any "Category C - Standard" frame
- 3 - For use with listed and labeled Warm Springs Mineral Composite 90 Minute frame system.

Certification body: Intertek Testing Services NA, Inc.

Initial registration: August 01, 2017

Date of expiry: December 31, 2019

Issue status: 4

Charles Meyers
Certification Manager
Name

Signature

17 Mar 2019
Date


Certificate of Compliance

You have been awarded:

Intertek Warnock Hersey Mark for fire resistant doors and door sets

Standard(s): UBC 7-2 (1997), ASTM E2074 (2004), UL 10(b) (2008), UL 10(c) (2009), CAN / ULC S104 (2010), NFPA 252 (2012), CAN / ULC S104 (2015)

Certificate number: WHI17 – 9354722



This is a certificate of compliance to certify that the bearer has successfully completed the requirements of the above scheme which include the testing of products, the initial assessment, and are subject to continuing annual assessments of their compliance and testing of samples of products taken from production (as applicable to the scheme) and has been registered within the scheme for the products detailed.

Organization:

Haseeb Rasoul FZC
P.O. Box 42327
Hamriyah Free Zone
Sharjah, United Arab Emirates

Product: Warm Springs 20-90 Min Fire Door Frame (SPEC ID 14775)

Composite Door frame for Installation in 20, 45, 60, or 90 Minute locations in steel/wood stud drywall or masonry openings

For details related to maximum dimensions and allowable configurations, see Appendix A (page 2 of 2 of this certificate)

Certification body: Intertek Testing Services NA, Inc.

Initial registration: August 01, 2017

Date of expiry: December 31, 2019

Issue status: 4

Charles Meyers
Certification Manager
Name

Signature

17 Mar 2019
Date

Certificate of Compliance WHI17 – 9354722

Appendix A

Description:

Category C - Proprietary Frames

Composite Door frame for Installation in 20, 45, 60, or 90 Minute locations in steel/wood stud drywall or masonry openings. A Category B or Neutral Pressure fire rated wood/composite door may be used depending on the application. Category G Edge Sealing System is not required for the frame. May be veneered, or faced with HPL. Frame may also be used as a communicating frame, and for fixed panel sidelites and transoms.

LIMITATIONS

Composite Frame Leg

Rating	Configuration	Max. Overall Opening	Min. Wall Thickness
20 Min. 45 Min. 60 Min. 90 Min.	Single Swing	4 ft. 0 in. wide 8 ft. 0 in. high	4-1/2 in
	Pairs	8 ft. 0 in. wide 8 ft. 0 in. high	4-1/2 in

MDF or Anti-Fire Composite Frame Leg

Rating	Configuration	Max. Overall Opening	Min. Wall Thickness
20 Min. 45 Min. 60 Min.	Single Swing	4 ft. 0 in. wide 8 ft. 0 in. high	4-1/2 in.
20 Min.	Pairs	7 ft. 0 in. wide 8 ft. 0 in. high	4-1/2 in

Wood Frame Leg

Rating	Configuration	Max. Overall Opening	Min. Wall Thickness
20 Min. 45 Min.	Single Swing	4 ft. 0 in. wide 8 ft. 0 in. high	4-1/2 in.

Each frame option noted above must be constructed in accordance with the specifications of the Manufacturing section of this Listing report.

www.intertek.com

The certificate and schedule are held in force by regular annual surveillance visits by Intertek Testing Services NA, Inc. and the reader or user should contact Intertek to validate its status. This certificate remains the property of Intertek Testing Services NA, Inc. and must be returned to them on demand. This Certificate is for the exclusive use of Intertek's Client and is provided pursuant to the Certification agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this certificate. Only the Client is authorized to permit copying or distribution of this certificate and then only in its entirety. Use of Intertek's Certification mark is restricted to the conditions laid out in the agreement. Any further use of the Intertek name for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. Initial Factory Assessments and Follow up Services are for the purpose of assuring appropriate usage of the Certification mark in accordance with the agreement, they are not for the purposes of production quality control and do not relieve the Client of their obligations in this respect.